

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	$\leq 0.5\%$	Conformity
 Breaking strength	ISO 10545-4	$\geq 35\text{N/MM}^2$	Conformity
 Abrasion resistance	ISO 10545-7		PEI 5-Sabbia PEI 4-Other Colors
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible sign of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5	$\leq 1300\text{ N min}$	Conformity
 Dynamic coefficient of friction	BOT 3000E	ANSI A137.1:2017	DCOF ≥ 0.42
 Slight Variation	See Below		V4



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.

BOTTEGA
ceramica e stile

www.bfceramics.com