









HYDE PARK HEXAGONS - BLENDS GLOSSY & MATTE BLEND

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7	MOHS	4
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable - Wall Tile Only	
 Slight Variation	See Below		V2

COLORS FEATURED IN THE HEXAGON BLENDS:

- Fossil - Shadow -



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK HEXAGONS - PATTERNS MATTE

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7	MOHS	5
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	ANSI A137.1-2017	DCOF ≥ 0.42
 Slight Variation	See Below		V2

COLORS FEATURED IN THE HEXAGON PATTERNS:

- Blend Pattern 1 - Blend Pattern 2 - Blend Pattern 3 - Blend Pattern 4 -



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK HEXAGONS - STONE GLASS CRYSTALLINE

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7	MOHS	9
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	ANSI A137.1-2017	DCOF ≥ 0.42
 Slight Variation	See Below		V2

COLORS FEATURED IN THE HEXAGON STONEGLASS:

- **Black** - **Gainsboro** - **White** -



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK HEXAGONS - HEX XL BLENDS POLISHED & MATTE BLEND

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7		PEI 1
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable - Wall Tile Only	
 Slight Variation	See Below		V2

COLORS FEATURED IN THE HEXAGON XL BLENDS:

- Fossil - Stone Glass Opalo Black -



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK HEXAGONS - XL STONE BLENDS CRYSTALLINE

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7	MOHS	9
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	ANSI A137.1-2017	DCOF ≥ 0.42
 Slight Variation	See Below		V2

COLORS FEATURED IN THE HEXAGON XL STONE BLENDS:

- Soft -



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK HEXAGONS - XL ZELIK GLOSSY & MATTE BLEND

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7		PEI 1
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable - Wall Tile Only	
 Slight Variation	See Below		V3

COLORS FEATURED IN THE HEXAGON XL ZELIK BLENDS:

- **Zelik** -



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK PENNY ROUNDS - BLENDS POLISHED & MATTE BLEND

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7		PEI 1
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable - Wall Tile Only	
 Slight Variation	See Below		V2

COLORS FEATURED IN THE PENNY ROUND BLENDS:

- **Nature Glass Opalo Black** - **Nature Glass Opalo White** -



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK PENNY ROUNDS - OPALO POLISHED

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7		PEI 1
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable	
 Slight Variation	See Below		V2

COLORS FEATURED IN THE PENNY ROUNDS OPALO:

- Opalo Black - Opalo White -



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK PENNY ROUNDS - SHINY POLISHED

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7		PEI 1
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable	
 Slight Variation	See Below		V2

COLORS FEATURED IN THE PENNY ROUND SHINY:

- Shiny Black - Shiny Dark Grey - Shiny Grey - Shiny Taupe - Shiny White -



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3



Substantial Variation

V4









FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com

HYDE PARK PENNY ROUNDS - VANGUARD POLISHED

QUALITY CHARACTERISTICS	NORM	STANDARDS	RESULT
 Water absorption of the body	ISO 10545-3	≤ 0.5%	None
 Breaking strength	ISO 10545-4		
 Abrasion resistance	ISO 10545-7	MOHS	4
 Frost resistance	ISO 10545-12	No samples must show ruptures or noticeable surface alteration	Conformity
 Chemical resistance	ISO 10545-13	No samples must show visible signs of chemical attack	Conformity
 Thermal shock resistance	ISO 10545-5		
 Dynamic coefficient of friction	BOT 3000E	Not Applicable	
 Slight Variation	See Below		V2

COLORS FEATURED IN THE PENNY ROUND VANGUARD:

- Forest Blue - Kara Beige - Kara Blue - Lungomore - Nordic Stone - Print - Saona -



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

The polished finish is recommended for wall coverings or for the floors of residential bathrooms. Specifically, floor coverings in this material must not be subjected to excessively heavy traffic and must never be in direct contact with outdoor areas. As is often the case with natural stones, any spots on the surface or any unevenness in shine are typical characteristics of the product, deriving from the process used.



www.bfceramics.com