

TIMELESS

QUALITY CHARACTERISTICS		NORM	REQUIRED STANDARDS	RESULT
	BODY WATER ABSORPTION	UNI EN ISO 10545-3	$\leq 0,5\%$	CONFORMITY
	BREAKING STRENGTH	UNI EN ISO 10545-4	$\geq 35 \text{ N/mm}^2$	CONFORMITY
	ABRASION RESISTANCE	UNI EN ISO 10545-7	-	White/Grey field tiles - IV Black field tile - III Decors - N/A
	FROST RESISTANCE	UNI EN ISO 10545-12	no samples must show ruptures or noticeable surface alteration	CONFORMITY
	CHEMICAL RESISTANCE	UNI EN ISO 10545-13	no samples must show visible signs of chemical attack	CONFORMITY
	THERMAL SHOCK RESISTANCE	UNI EN ISO 10545-5	-	CONFORMITY
	DINAMIC COEFFICIENT OF FRICTION	BOT 3000-E	DCOF $\geq 0,42$	$\geq 0,42$
	SHADE VARIATION	see below	-	All colors field tiles - V2 Decors - N/A



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

MADE IN ITALY



www.bfceramics.com

MYSTIQUE

QUALITY CHARACTERISTICS		NORM	REQUIRED STANDARDS	RESULT
	BODY WATER ABSORPTION	UNI EN ISO 10545-3	$\leq 0,5\%$	CONFORMITY
	BREAKING STRENGTH	UNI EN ISO 10545-4	$\geq 35 \text{ N/mm}^2$	CONFORMITY
	ABRASION RESISTANCE	UNI EN ISO 10545-7	-	Grigio field tile - IV Decors - N/A
	FROST RESISTANCE	UNI EN ISO 10545-12	no samples must show ruptures or noticeable surface alteration	CONFORMITY
	CHEMICAL RESISTANCE	UNI EN ISO 10545-13	no samples must show visible signs of chemical attack	CONFORMITY
	THERMAL SHOCK RESISTANCE	UNI EN ISO 10545-5	-	CONFORMITY
	DINAMIC COEFFICIENT OF FRICTION	BOT 3000-E	DCOF $\geq 0,42$	$\geq 0,42$
	SHADE VARIATION	see below	-	All colors field tiles - V2 Decors - N/A



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

MADE IN ITALY



www.bfceramics.com