



Porcelain Pavers Installation Guide

Dear Customer,

This brief installation guide will provide you or the installer with a manual on how to properly install the B&F Ceramics 2 cm Porcelain Pavers. The tips and guide lines listed in this document are recommendations based on typical masonry or installation practices. Consulting your local codes department for their requirements is highly recommended as installation methods may vary from region to region. If you have questions, please feel free to contact us at 540-286-3000 or visit the factories' website www.florim.com for more information and tips.

Thank You,
The B&F Family

Installing on Gravel or Sand

Best used for Gardens, Courtyards, Patios, Gazebos, Walkways, & More.



- Be sure to even out & level the resting area
- Lay the tile piece on the gravel or sand, allowing a 1 cm or larger gap between each piece
- Use a rubber hammer to eliminate any unevenness
- Use your gravel or sand to fill in the joints and provide better stability to the surface

WARNING: Verify that the level of tile is in line with the level of the gravel layer in order to prevent the tile from shifting. This system cannot be installed for vehicle traffic.

Installing on Grass

Best used for Gardens, Gazebos, Walkways, Perimeter of Pools & More.



- Remove the soil below the area where the tile piece will be laid, roughly 5-7 cm thick
- In the removed soil area, apply a bed of gravel of 3-4 cm thick, compact the foundation
- Rest the tile piece(s) with at least a 1 cm gap & use a rubber hammer to remove any unevenness

WARNING: Ensure that the level of the tile is equal to the level of the grassy surface in order to prevent damage during mowing. This system cannot be installed for vehicle traffic.

Installing with Thin-Set over Concrete

Best used for Driveways, Garages, Sidewalks, Industrial Areas & More.



Before installing please consult the TCNA Handbook.

- Spread an approved exterior grade thin-set mortar over the concrete using the correct sized notched trowel
- Lay the pavers on the thin-set with minimum 1/8" to 3/16" joint spacing where the area is not large enough to require expansion joints, or with 3/8" spacing where expansion joints are present
- After the thin-set has dried, grout the pavers with an approved exterior grade grout

Additional Information

- Porcelain Stoneware will not change color or deteriorate over time
- Chemical Resistant. (i.e pool additives, household detergents, etc.)
- Weather Resistant; Rain, Wind, Salt, Mildew, Etc.
- Non-Slip
- Easy to clean
- Will not scratch
- The material can be easily re-positioned or moved if not glued.
- Made in Italy



www.bfceramics.com