

ZERA ANNEX GLAZED PORCELAIN



ZERA ANNEX GLAZED PORCELAIN



12 x 24 in (29.8 x 60 cm) ZERA ANNEX OYSTER RECTIFIED PORCELAIN TILE
MATTE 4500-0716-1



3 x 24 in (7.2 x 60 cm) ZERA ANNEX OYSTER PORCELAIN BULLNOSE
MATTE 4502-0262-1



2 x 2 in (5 x 5 cm) ZERA ANNEX OYSTER
PORCELAIN MOSAICS
MATTE 4501-0308-1



12 x 24 in (29.8 x 60 cm) ZERA ANNEX OLIVE RECTIFIED PORCELAIN TILE
MATTE 4500-0715-1



3 x 24 in (7.2 x 60 cm) ZERA ANNEX OLIVE PORCELAIN BULLNOSE
MATTE 4502-0261-1



2 x 2 in (5 x 5 cm) ZERA ANNEX OLIVE
PORCELAIN MOSAICS
MATTE 4501-0306-1

ZERA ANNEX GLAZED PORCELAIN



12 x 24 in (29.8 x 60 cm) ZERA ANNEX BIANCO RECTIFIED PORCELAIN TILE
MATTE 4500-0712-1



3 x 24 in (7.2 x 60 cm) ZERA ANNEX BIANCO PORCELAIN BULLNOSE
MATTE 4501-0259-1



2 x 2 in (5 x 5 cm) ZERA ANNEX BIANCO
PORCELAIN MOSAICS
MATTE 4501-0302-1



12 x 24 in (29.8 x 60 cm) ZERA ANNEX SILVER RECTIFIED PORCELAIN TILE
MATTE 4501-0718-1



3 x 24 in (7.2 x 60 cm) ZERA ANNEX SILVER PORCELAIN BULLNOSE
MATTE 4502-0264-1



2 x 2 in (5 x 5 cm) ZERA ANNEX SILVER
PORCELAIN MOSAICS
MATTE 4501-0312-1

ZERA ANNEX GLAZED PORCELAIN



12 x 24 in (29.8 x 60 cm) ZERA ANNEX CARBON RECTIFIED PORCELAIN TILE
MATTE 4500-0714-1



3 x 24 in (7.2 x 60 cm) ZERA ANNEX CARBON PORCELAIN BULLNOSE
MATTE 4502-0260-1



2 x 2 in (5 x 5 cm) ZERA ANNEX CARBON
PORCELAIN MOSAICS
MATTE 4501-0304-1

ZERA ANNEX GLAZED PORCELAIN

PACKAGING INFORMATION

DESCRIPTION	LBS/BOX	KGS/BOX	PCS/BOX	SQFT/BOX	M²/BOX	BXS/SKD	SQFT/SKID	M²/SKID
ZERA ANNEX								
12 x 24 in (29.8 x 60 cm) ZERA ANNEX RECTIFIED PORCELAIN TILE	64.06	29.06	8	15.5	1.44	32	496	46.08
1 x 6 in (2.5 x 15 cm) ZERA ANNEX STACKED MOSAICS	41.11	18.65	10	10	0.9	45	450	40.5
2 x 2 in (5 x 5 cm) ZERA ANNEX PORCELAIN MOSAICS	41.24	18.71	10	10	0.9	45	450	40.5
3 x 24 in (7.2 x 60 cm) ZERA ANNEX CARBON PORCELAIN BULLNOSE	41.8	18.96	20	N/A	N/A	56	1120 pcs.	1120 pcs.

TECHNICAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	12 x 24 in (29.8 x 60 cm)
			MATTE
THICKNESS		mm – in	9 mm
WATER ABSORPTION	ASTM C-373 / EN ISO 10545-3	(%)	≤ 0.5
ABRASION RESISTANCE	ASTM C-1027 / EN ISO 10545-7	(PEI)	4
SCRATCH HARDNESS		(Mohs)	7
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 600
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A Resistant
STAIN RESISTANCE	EN ISO 10545-14		Class 5
FROST RESISTANCE	EN ISO 10545-12 / ASTM C1026		Pass
DCOF (WET)	ANSI B101.3		≥ 0.42
R VALUE			(-)
SHADE VARIATION			V1