

STATION

PACKAGING INFORMATION

DESCRIPTION	ITEM CODE				LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	IVORY	PEARL	ASH	SHADOW					
32" x 32" STATION HD RECTIFIED PORCELAIN TILE	68-325	68-326	68-327	68-329	73.81	2	13.78	32	440.96
12" x 24" STATION HD RECTIFIED PORCELAIN TILE	69-474	69-475	69-476	69-477	59.46	8	15.52	32	496.64
10" x 24" STATION HALF HEXAGON HD PORCELAIN TILE	64-001	64-002	64-003	64-004	50.54	8	10.12	32	322.38
3" x 24" STATION HD PORCELAIN BULLNOSE	69-996	69-997	69-998	69-999	33.45	15	n/a	56	840 pcs.
2" x 2" STATION HD PORCELAIN MOSAICS	63-666	63-667	63-668	63-669	38.45	10	9.62	48	461.88

GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	32" x 32"	12" x 24"	10" x 24"
THICKNESS		mm – in	11.5 mm – 7/16"	8.4 mm – 11/32"	8.4 mm – 11/32"
WATER ABSORPTION	ASTM C-373 / EN ISO 10545-3	(%)	≤ 0.5	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	ASTM C-1027 / EN ISO 10545-7	(PEI)	4	4	4
SCRATCH HARDNESS		(Mohs)	9	9	9
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 360	≥ 360	≥ 360
STAIN RESISTANCE	EN ISO 10545-14		Class 5	Class 5	Class 5
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Res.	Class A – Res.	Class A – Res.
FROST RESISTANCE	EN ISO 10545-12		Resistant	Resistant	Resistant
DCOF (WET)	ANSI B101.3		≥ 0.45	≥ 0.45	≥ 0.45
SHADE VARIATION			V3	V3	V3

* While the information has been presented with all due care, Anatolia Tile and Stone Inc. does not warrant the information is free from errors or omission. Actual colors may vary depending on product.



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

www.bfceramics.com

2005 International Parkway Fredericksburg, VA 22406 | Phone: 540-286-3000 | Fax: 540-286-3010