

# Zera Annex

| QUALITY CHARACTERISTICS                                                                                            | NORM            | REQUIRED STANDARDS | RESULT      |
|--------------------------------------------------------------------------------------------------------------------|-----------------|--------------------|-------------|
|  Water absorption of the body     | ISO<br>10545-3  | $< 0.5$            | Conforms    |
|  Breaking strength                | ISO<br>10545-4  | $\geq 600$         | Conforms    |
|  Abrasion resistance              | ISO<br>10545-7  | PEI 4              | Conforms    |
|  Frost resistance                 | ISO<br>10545-12 |                    | Resistant   |
|  Chemical resistance              | ISO<br>10545-13 | Class A            | Resistant   |
|  Thermal shock resistance         | ISO<br>10545-5  |                    |             |
|  Dynamic coefficient of friction | BOT<br>3000     | ANSI<br>A137.1     | $\geq 0.42$ |
|  Slight Variation               |                 |                    |             |



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

FOR THE BEST PRODUCT LAYING RESULTS, MATERIAL FROM AT LEAST THREE BOXES SHOULD BE MIXED

[www.bfceramics.com](http://www.bfceramics.com)

2005 International Parkway Fredericksburg, VA 22406 | Phone: 540-286-3000 | Fax: 540-286-3010